

HP: 1/3 - 15

Frame: 56C - 215T

RPM: 3600/1800/1200

Pole: 2 / 4 / 6

3Φ Volt: 208-230/ 460V

Encl: (TEFC) IP 55



Standard Features :

- NEMA Premium Efficiency
- Dual Voltage - Three Phase 230/460V
- 3600/1800/1200 RPM - 2/4/6 Pole
- Inverter Duty -15:1 Constant Torque (MG1 Part 31)
- Totally Enclosed Fan Cooled IP 55 Protection
- VPI Lap wound Stator with Anti-fungal Coating
- Double Lip Oil Seal on DE & ODE
- 1.25 SF - 143T and Up (1.15 SF - 56C Frame)
- 50 Hz Capable at 1.0 SF
- 40° C Ambient Temperature Rating
- 1045 Carbon Steel Shaft
- Multi-mount Frame with Removable Feet
- Oversized Drive End Bearing
- One-Way Brass Condensation Drains
- Aluminum Conduit Box 90° Rotatable
- Class F Insulation System with Class H Stator
- F1, F2, F3 Box Position Convertible (Shipped F1)
- Class 1, Division 2, Group C & D Compliant
- Installation up to 3300 ft Altitude
- 36 Month Warranty from Purchase Date

HP	Sync Speed	Model Number	List Price	
			Rigid Base	C - Face
1/3	3600	GR3-AL-TF-56C-2-B-D-.33	---	298
	1800	GR3-AL-TF-56C-4-B-D-.33	---	291
1/2	3600	GR3-AL-TF-56C-2-B-D-.5	---	314
	1800	GR3-AL-TF-56C-4-B-D-.5	---	306
3/4	3600	GR3-AL-TF-56C-2-B-D-.75	---	334
	1800	GR3-AL-TF-56C-4-B-D-.75	---	332
1	3600	GR3-AL-TF-56C-2-B-D-1	---	351
	1800	GR3-AL-TF-56C-4-B-D-1	---	375
	1800	GR3-AL-TF-143T-4-B-D-1	422	474
	1200	GR3-AL-TF-145T-6-B-D-1	475	527
1.5	3600	GR3-AL-TF-56C-2-B-D-1.5	---	367
	1800	GR3-AL-TF-56C-4-B-D-1.5	---	453
	3600	GR3-AL-TF-143T-2-B-D-1.5	444	496
	1800	GR3-AL-TF-145T-4-B-D-1.5	459	511
	1200	GR3-AL-TF-182T-6-B-D-1.5	560	664
2	3600	GR3-AL-TF-56C-2-B-D-2	---	391
	1800	GR3-AL-TF-56C-4-B-D-2	---	479
	3600	GR3-AL-TF-145T-2-B-D-2	492	544
	1800	GR3-AL-TF-145T-4-B-D-2	491	543
	1200	GR3-AL-TF-184T-6-B-D-2	656	760
3	3600	GR3-AL-TF-56C-2-B-D-3	---	504
	3600	GR3-AL-TF-182T-2-B-D-3	651	755
	1800	GR3-AL-TF-182T-4-B-D-3	639	743
	1200	GR3-AL-TF-213T-6-B-D-3	901	1034
5	3600	GR3-AL-TF-184T-2-B-D-5	714	818
	1800	GR3-AL-TF-184T-4-B-D-5	721	825
	1200	GR3-AL-TF-215T-6-B-D-5	1175	1308
7.5	3600	GR3-AL-TF-213T-2-B-D-7.5	1003	1136
	1800	GR3-AL-TF-213T-4-B-D-7.5	1017	1150
10	3600	GR3-AL-TF-215T-2-B-D-10	1150	1283
	1800	GR3-AL-TF-215T-4-B-D-10	1163	1296
15	3600	GR3-AL-TF-215T-2-B-D-15	1756	1825

